

PA amplifier with USB/SD/MP3 recorder/player

BENEFITS

Versatile and complete equipment integrating all the necessary elements of a professional sound installation: microphone and line inputs, auxiliary input, USB/SD/MP3 recorder/player, mixer and amplifier.

Designed for use in PA installations with 100 V line speakers or mono installations with low impedance speakers.

Speaker zone selector with independent volume control.

Audio inputs with market standard XLR, jack and RCA connections.

Speaker connectors with screw terminals, secure and easy to connect.

High sound quality.

Compact size, for desktop or 19" rack.

APPLICATIONS

PA and background music installations with 100 V or low impedance line loudspeakers. Shopping premises, educational centres, monuments, exhibitions, bars, restaurants, etc.

TECHNICAL DATA

240 W RMS

Microphone inputs with volume control

4 selectable speaker zones with independent volume control

Priority with adjustable level on input 1

Tone controls

100 V, 70 V, 25 V and 4 Ohm outputs

Mains or 24 V DC battery power supply



MA-245GU

	P. A. amplifier. USB/SD/MP3 recorder/player.
FEATURES	4 selectable loudspeaker zones with independent volume control. Phantom power. Priority paging.
POWER	360 W maximum, 240 W RMS
RESPONSE	80-16 000 Hz ±3 dB
DISTORTION	Harmonic: < 1%

INPUTS	4 balanced mics./lines, combo (XLR and 6.3 mm jack) 600 Ohm 2 mV and 47000 Ohm 150 mV, switchable 1 auxiliary, 2 x RCA 47000 Ohm 300 mV 1 amp in, RCA 10000 Ohm 1 V 1 tel. input, screw terminals 600 Ohm 100 mV
OUTPUTS	1 line out, 2 x RCA 47000 Ohm 1V 1 pre out, RCA 600 Ohm 1 V 1 monitor, screw terminals 600 Ohm, 775 mV and 1 W 8 Ohm (aux. input)
CONTROLS	Tone: Bass: \pm 10 dB Treble: \pm 10 dB Volume: Inputs 1-4, aux, general volume and USB/SD/MP3 player
PLAYER	USB/SD/MP3 recorder/player
PHANTOM	24 V in mics. 1 to 4, selectable
PRIORITY	Tel. input and mic. 1 depending on signal level, selectable
ZONE SELECTOR	4 selectable speaker zones with independent volume control, maximum 120 W per zone
IMPEDANCE	4 Ohm and 100, 70 and 25 V lines, screw terminals
POWER SUPPLY	230/115 V AC, 600 W and 24 V DC, 312 W
DIMENSIONS	420 x 89 x 300 mm depth. 2 x 19" U rack
WEIGHT	11.7 kg
OPTIONAL	MA-2N: mounts for assembly in 19" rack