

Low impedance mono attenuator for recessed or surface mounting.

**Benefits:**

FONESTAR's own minimalist design, taking into account the market's needs and ensuring that they will blend in with any installation, whether domestic or professional.

Ergonomically designed 6-position potentiometer with an off switch, which allows for easy operation.

The transformer attenuator provides better sound quality and volume control accuracy.

Thanks to its standard measures, it can be embedded with square and round universal boxes for cardboard and plaster partitions (Pladur).

They can also be installed on the surface along with the DOT-BOX surface installation boxes, available in black or white.

This whole range is supplied in white, however, for installations requiring black attenuators, the black panel mod. DOT-01N, available separately, is easily interchangeable with the white one.

**Applications (common to the whole series):**

PA and voice evacuation systems, large and small shops, shopping centres, hotels, cafeterias, game rooms, household use, etc.

**Technical data:**

Attenuator with low impedance mono transformer

Low Z for speakers 4-8 Ohm

6-position dimmer potentiometer with an off switch

Power: 60 W

Colour: White



**DOT-60M**

CHARACTERISTICS	Low impedance mono transformer attenuator for recessed or surface mounting. The transformer provides better sound quality and volume control accuracy.
POWER	60 W maximum
OUTPUTS	Low Z for 4-8 Ohm speakers
DIMENSIONS	Total: 83 x 83 x 50 mm depth Insert: 50 x 50 x 38 mm depth
CONTROLS	6 dimming positions and off switch
WEIGHT	0.2 kg
	For standard universal square box, round for plasterboard partitions and for surface installation box mod. DOT-BOX. Distance between screws: 60 mm